

RECYCLED PVC : OK
GLASS FIBER TISSUE : NO
PURGUARD : OK

TECHNICAL PROPERTIES		
SPECIFICATION	STANDARD	PRODUCT
Back Layer		TX150S
Total thickness	EN ISO 24346	1.4mm (min:-0.10mm max: 0.13mm)
Wear layer thickness	EN ISO 24340	0.03mm (max: +%13 min: -%10)
Mass per Unit Area	EN ISO 23997	1525 g/m2 (max: +%13 min: -%10)
Roll width	EN ISO 24341	Min:200cm
Roll length	EN ISO 24341	Min: 30 m
PERFORMANCE		
Wear Layer Group	EN 660-2	GROUP T
Dimensional Stability	EN ISO 23999	≤%0.8
Curling	EN ISO 23999	Max:12mm
Residual indentation	EN ISO 24343-1	max:≤0.3mm
Flexibility	EN ISO 24344	No Crack

Standard products are produced with recycled PVC. Chemical structure, ingredients and chemical behaviours can not be warranted. It is optional to use only virgin raw material upon your request in case you like to have a declaration for chemical ingredients and chemical behaviors. Please kindly contact your supplier for further information.

* Sipariş geçmeden önce, lütfen güncel TDS verilerini talep edin.

* Before placing an order, please request up-to-date TDS data.